## **PRODUCT: HOT SHOT**

## SECTION 01: PRODUCT AND COMPANY INFORMATION

MANUFACTURER/SUPPLIER
MANUFACTURER'S/SUPPLIERS ADDRESS
PRODUCT NAME
PRODUCT USE
EMERGENCY PHONE NUMBER

LES INVESTISSEMENTS B.S.C. INC. 109 IBER RD.,UNIT #3 OTTAWA, ON K2S 0X5 613-744-8896 HOT SHOT SILICONE TIRE CLEANER CANUTECH 613-996-6666

# SECTION 02: HAZARDS IDENTIFICATION



				$\sim$
ROUTE OF ENTRY:				
SKIN CONTACT		E MODERATE SKIN II	RRITATION.	
SKIN ABSORPTION	N.AV.			
EYE CONTACT		MAY BE IRRITATING	TO THE EYE. MAY B	E IRRITATING TO
	THE EYES.			
INHALATION	VAPOURS /	ARE MODERATELY II	RRITATING TO RESP	PIRATORY
	PASSAGES			
INGESTION	INGESTION	OF THIS PRODUCT	MAY CAUSE HEADA	CHE, DIZZINESS,
	FATIGUE A	ND CENTRAL NERVO	OUS SYSTEM DEPRE	SSION.
EFFECTS/SYMPTOMS OF ACUTE EXPOSURE	EXPOSURE	MAY OCCUR VIA IN	HALATION, INGESTI	ON, SKIN
	ABSORPTIC	ON AND SKIN OR EYI	E CONTACT. RESPIR	ATORY
	IRRITATION	I SIGNS AND SYMPT	OMS MAY INCLUDE	A TEMPORARY
	BURNING S	SENSATION OF THE N	NOSE AND THROAT,	COUGHING,
	AND/OR DI	FICULTY BREATHIN	G. SKIN IRRITATION	SIGNS AND
	SYMPTOMS	S MAY INCLUDE A BU	JRNING SENSATION	, REDNESS,
	SWELLING	AND/OR BLISTERS.	EYE IRRITATION SIG	GNS AND
	SYMPTOMS	S MAY INCLUDE A BL	JRNING SENSATION	, REDNESS,
	SWELLING	AND/OR BLURRED	/ISION. IF MATERIAL	ENTERS LUNGS,
	SIGNS AND	SYMPTOMS MAY IN	CLUDE COUGHING,	CHOKING,
	WHEEZING	, DIFFICULTY IN BRE	ATHING, CHEST CO	NGESTION,
	SHORTNES	S OF BREATH, AND/	OR FEVER.	
EFFECTS/SYMPTOMS OF CHRONIC EXPOSURE	PROLONGE	ED AND REPEATED C	CONTACT WITH SKIN	I CAN CAUSE
	DEFATTING	AND DRYING OF TH	<b>IE SKIN RESULTING</b>	IN SKIN
	IRRITATION	AND DERMATITIS.	PROLONGED EXPOS	SURE TO HIGH
	VAPOUR C	ONCENTRATION CAN	N CAUSE HEADACHE	E, DIZZINESS,
	NAUSEA, B	LURED VISION AND	CENTRAL NERVOUS	SYSTEM
	DEPRESSI	ON.		
MEDICAL CONDITIONS GENERALLY	PREEXISTI	NG EYE, SKIN AND R	ESPIRATORY DISOF	RDERS MAY BE
AGGRAVATED BY EXPOSURE	AGGRAVAT	ED BY EXPOSURE T	O THIS PRODUCT.	
SECTION 03: COMPOSITION / INFOR	RMATION OF	N INGREDIENTS H	AZARDS IDENTIFIC	CATION
	24	<b>T</b> 1 \ /		1.050
HAZARDOUS INGREDIENTS C.A.S. #	%	TLV	LD50	LC50
TRADE SECRET		SEE SECTION 11	N.AV.	N.AV.
		SEE SECTION IT	IN./TV.	IN.~V.

# SECTION 04: FIRST AID MEASURES

SKIN CONTACT	FLUSH AFFECTED SKIN WITH GENTLY FLOWING LUKEWARM WATER FOR AT LEAST 20 MINUTES AND REMOVE CONTAMINATED CLOTHING WHILE RINSING. WASH CONTAMINATED SKIN WITH MILD SOAP AND WATER FOR 15 MINUTES. IF IRRITATION OCCURS AND PERSISTS,
	OBTAIN MEDICAL ATTENTION.
EYE CONTACT	FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. OBTAIN MEDICAL ATTENTION AS SOON AS
	POSSIBLE AFTER FIRST AID HAS BEEN INITIATED AND COMPLETED.
INHALATION	REMOVE VICTIM FROM FURTHER EXPOSURE AND RESTORE
	BREATHING, IF REQUIRED. OBTAIN MEDICAL ATTENTION.
INGESTION	DO NOT INDUCE VOMITING. GUARD AGAINST ASPIRATION INTO
	LUNGS BY HAVING THE INDIVIDUAL TURN ON TO THEIR LEFT SIDE. IF

NOTES TO PHYSICIAN	VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IMMEDIATELY. THE MAIN HAZARD FOLLOWING ACCIDENTAL INGESTION IS
	ASPIRATION OF THE LIQUID INTO THE LUNGS PRODUCING CHEMICAL PNEUMONITIS. IF MORE THAN 2.0 ML/KG (NAPHTHA (PETROLEUM), HEAVY ALKYLATE) HAS BEEN INGESTED, VOMITING SHOULD BE INDUCED WITH SUPERVISION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE VOMITING, GASTRIC LAVAGE WITH A CUFFED ENDOTRACHEAL TUBE SHOULD BE CONSIDERED.

### **SECTION 05: FIRE FIGHTING MEASURES**

MEANS OF EXTINCTION/EXTINGUISHING MEDIA: FLASH POINT UPPER FLAMMABLE LIMIT (% BY VOLUME) LOWER FLAMMABLE LIMIT (% BY VOLUME) AUTO-IGNITION TEMPERATURE SPECIAL FIRE FIGHTING PROCEDURES SPECIAL FIRE FIGHTING PROCEDURES EXPLOSION DATA SENSITIVITY TO MECHANICAL IMPACT SENSITIVITY TO STATIC DISCHARGE	SEE FLASH POINT. DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG. WATER SPRAY. DO NOT USE WATER IN A JET. >51 (C) N.AV. N.AV. VAPOURS FORM A FLAMMABLE/EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS. DO NOT ENTER CONFINED FIRE SPACE WITHOUT ADEQUATE PROTECTIVE CLOTHING AND AN APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. EXCLUDE AIR. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER. CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOUR PRESSURE BUILD UP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE. CAUTION-COMBUSTIBLE. N.AV. N.AV. N.AV.
HAZARDOUS COMBUSTION PRODUCTS	CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

### SECTION 06: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES ....... ISSUE WARNING "COMBUSTIBLE". ELIMINATE ALL SOURCES OF IGNITION. HANDLING EQUIPMENT MUST BE GROUNDED. ISOLATE HAZARD AREA AND RESTRICT ACCESS. TRY TO WORK UP WIND OF SPILL. AVOID DIRECT CONTACT WITH MATERIAL. WEAR APPROPRIATE BREATHING APPARATUS (IF APPLICABLE) AND PROTECTIVE CLOTHING. STOP LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN LAND SPILLS; CONTAIN WATER SPILLS BY BOOMING. FOR LARGE SPILLS REMOVE BY MECHANICAL MEANS AND PLACE IN CONTAINERS. ABSORB RESIDUE OR SMALL SPILLS WITH ABSORBENT MATERIAL AND REMOVE TO NON-LEAKING CONTAINERS FOR DISPOSAL. RECOMMENDED MATERIALS: CLAY OR SAND. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. DISPOSE OF RECOVERED MATERIAL AS NOTED UNDER DISPOSAL CONSIDERATIONS.

# SECTION 07: HANDLING AND STORAGE

STORAGE REQUIREMENTS.....

AND TURN OFF OTHER SOURCES OF IGNITION PRIOR TO USE AND UNTIL ALL VAPOURS ARE GONE. VAPOURS MAY ACCUMULATE AND TRAVEL TO DISTANT IGNITION SOURCES AND FLASHBACK. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS PRODUCT RESIDUES. FIXED EQUIPMENT AS WELL AS TRANSFER CONTAINERS AND EQUIPMENT SHOULD BE GROUNDED TO PREVENT ACCUMULATION OF STATIC CHARGE. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS. AVOID BREATHING VAPORS AND PROLONGED OR REPEATED CONTACT WITH SKIN. AIR-DRY CONTAMINATED CLOTHING IN A WELL VENTILATED AREA BEFORE LAUNDERING. WEAR APPROPRIATE RESPIRATORY PROTECTION AND PROTECTIVE CLOTHING. LAUNDER CONTAMINATED CLOTHING PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE. DO NOT PRESSURIZE DRUM CONTAINERS TO EMPTY THEM. STORE IN A COOL, DRY, WELL VENTILATED AREA, AWAY FROM HEAT AND IGNITION SOURCES. USE EXPLOSION PROOF VENTILATION TO PREVENT VAPOUR ACCUMULATION. KEEP CONTAINER TIGHTLY CLOSED.

## SECTION 08: EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROL	MAKE UP AIR SHOULD ALWAYS BE SUPPLIED TO BALANCE AIR EXHAUSTED (EITHER GENERALLY OR LOCALLY). ELECTRICAL AND MECHANICAL EQUIPMENT SHOULD BE EXPLOSION-PROOF. CONCENTRATIONS IN AIR SHOULD BE MAINTAINED BELOW THE RECOMMENDED THRESHOLD LIMIT VALUE IF UNPROTECTED PERSONNEL ARE INVOLVED. FOR PERSONNEL ENTRY INTO CONFINED SPACES (I.E. BULK STORAGE TANKS) A PROPER CONFINED SPACE ENTRY PROCEDURE MUST BE FOLLOWED INCLUDING VENTILATION AND TESTING OF TANK ATMOSPHERE. LOCAL VENTILATION RECOMMENDED WHERE MECHANICAL VENTILATION IS INEFFECTIVE IN CONTROLLING AIRBORNE CONCENTRATIONS BELOW THE RECOMMENDED OCCUPATIONAL EXPOSURE LIMIT. MECHANICAL VENTILATION IS RECOMMENDED FOR ALL INDOOR SITUATIONS TO CONTROL FUGITIVE EMISSIONS.
PERSONAL PROTECTIVE EQUIPMENT:	
SKIN PROTECTION	IMPERVIOUS GLOVES (VITON, NITRILE) SHOULD BE WORN AT ALL TIMES WHEN HANDLING THIS MATERIAL. IN CONFINED SPACES OR WHERE THE RISK OF SKIN EXPOSURE IS MUCH HIGHER, IMPERVIOUS CLOTHING SHOULD BE WORN.
EYE/FACE PROTECTION	CHEMICAL SAFETY GOGGLES AND/OR FULL FACE SHIELD TO PROTECT EYES AND FACE, IF PRODUCT IS HANDLED SUCH THAT IT COULD BE SPLASHED INTO EYES.
RESPIRATORY PROTECTION	IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE AN APPROPRIATE NIOSH-APPROVED RESPIRATOR. USE A NIOSH- APPROVED CHEMICAL CARTRIDGE RESPIRATOR WITH ORGANIC VAPOUR CARTRIDGES OR USE A NIOSH-APPROVED SUPPLIED-AIR RESPIRATOR. FOR HIGH AIRBORNE CONCENTRATIONS, USE A NIOSH-APPROVED SUPPLIED-AIR RESPIRATOR, EITHER SELF- CONTAINED OR AIRLINE BREATHING APPARATUS, OPERATED IN POSITIVE PRESSURE MODE.
WORK/HYGIENE PRACTICES	PROVIDE AN EYEWASH STATION IN THE AREA. SAFETY SHOWERS SHOULD BE AVAILABLE FOR EMERGENCY USE.

### SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE	LIQUID
APPEARANCE & ODOUR	MILKY WHITE COLOUR – NEW CAR SCENT
ODOUR THRESHOLD	N.AV.
SPECIFIC GRAVITY	N.AV.
VAPOUR PRESSURE (MMHG)	N.AV.
VAPOUR DENSITY (AIR=1)	N.AV.
EVAPORATION RATE	N.AV.

### **PRODUCT: HOT SHOT**

BOILING POINT	N.AV.
FREEZING/MELTING POINT	N.AV.
PH	N.AV.
SOLUBILITY IN WATER (% W/W)	SOLUBLE.
COEFFICIENT OF WATER/OIL DISTRIBUTION	N.AV.

### SECTION 10: STABILITY AND REACTIVITY

STABILITY	STABLE UNDER NORMAL OPERATING CONDITIONS.
CONDITIONS TO AVOID	AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL IGNITION
	SOURCES.
INCOMPATIBILITY (MATERIALS TO AVOID)	STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCT	SEE HAZARDOUS COMBUSTION PRODUCTS.
HAZARDOUS POLYMERIZATION	WILL NOT OCCUR.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **SECTION 12: ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION

N.AV.

B3

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL

IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND FEDERAL REGULATIONS.

#### **SECTION 14: TRANSPORT INFORMATION**

PROPER SHIPPING NAME	NOT REGULATED IF <450 L.
TDG CLASSIFICATION	NOT REGULATED IF <450 L.
UN NUMBER	NOT REGULATED IF <450 L.
PACKGING GROUP	NOT REGULATED IF <450 L.

. . . . . . . . . . . . . . . . . .

#### **SECTION 15: REGULATORY INFORMATION**

WHMIS CLASSIFICATION
CPR COMPLIANCE

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

## **SECTION 16: OTHER INFORMATION**

PREPARATION INFORMATION .....

PREPARED BY: REGULATORY AFFAIRS, TELEPHONE - (613)-744-8896 PREPARATION DATE: JULY 1, 2016

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE Page 4