SAFETY DATA SHEET

PRODUCT: PRISM Page 1

SECTION 01: PRODUCT AND COMPANY INFORMATION

MANUFACTURER/SUPPLIER LES INVESTISSEMENTS B.S.C. INC.

PRODUCT NAME PRISM

PRODUCT USE ACRYLIC WAX

EMERGENCY PHONE NUMBER CANUTECH 613-996-6666

SECTION 02: HAZARDS IDENTIFICATION



LC50

SKIN CONTACT PROLONGED EXPOSURE NOT LIKELY TO CAUSE SIGNIFICANT SKIN IRRITATION. PROLONGED SKIN CONTACT IS UNLIKELY TO RESULT IN ABSORPTION OF HARMFUL AMOUNTS.

SKIN ABSORPTION N.AV.

EYE CONTACT MAY CAUSE MODERATE EYE IRRITATION. CORNEAL INJURY IS UNLIKELY.

INHALATION NO ADVERSE EFFECTS ARE ANTICIPATED FROM SINGLE EXPOSURE

TO VAPOR.

INGESTION LOW TOXICITY. SMALL AMOUNTS SWALLOWED INCIDENTAL TO

NORMAL HANDLING OPERATIONS ARE NOT LIKELY TO CAUSE INJURY. SWALLOWING LARGER AMOUNTS MAY CAUSE INJURY.

EFFECTS/SYMPTOMS OF ACUTE EXPOSURE SEE ABOVE. EFFECTS/SYMPTOMS OF CHRONIC EXPOSURE SEE ABOVE. MEDICAL CONDITIONS GENERALLY N.AV.

C.A.S. #

AGGRAVATED BY EXPOSURE.....

HAZARDOUS INGREDIENTS

ROUTE OF ENTRY:

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS HAZARDS IDENTIFICATION

TLV

DIETHYLENE GLYCOL 111-90-0 1-5 N.AV. 1920 Mg/Kg INHALATION (ORAL, RAT) LC50 (RAT) > 5240 MG/M3 4 H 4200 ML/KG (DERMAL,

(DERMAL, RABBIT) 6 ML/KG (DERMAL, RAT)

LD50

TRIS(2-BUTOXYETHYL) 78-51-3 1-5 N.AV. 3 G/KG (ORAL, N.AV. PHOSPHATE RODENT - RAT)

RODENT - RAT) 180 MG/KG (INTRAVENOUS, RODENT -MOUSE).

SECTION 04: FIRST AID MEASURES

AND GET MEDICAL ATTENTION IMMEDIATELY AFTER FLUSHING.

REMOVE CONTACT LENSES, IF WORN.

INHALATION....... MOVE PERSON TO FRESH AIR. IF IRRITATION PERSISTS, SEEK

MEDICAL ATTENTION.

MEDICAL ATTENTION. IF VOMITING OCCURS SPONTANEOUSLY, KEEP

PRODUCT: PRISM Page 2

HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS.

NOTES TO PHYSICIAN.....

NO SPECIFIC ANTIDOTE. TREATMENT OF EXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITION OF THE PATIENT.

SECTION 05: FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY.....

NON-FLAMMABLE.

MEANS OF EXTINCTION/EXTINGUISHING MEDIA: ...

WATER FOG OR FINE SPRAY, CARBON DIOXIDE, DRY CHEMICAL, FOAM. ALCOHOL RESISTANT FOAMS (ATC TYPE) ARE PREFERRED IF AVAILABLE. GENERAL PURPOSE SYNTHETIC FOAMS (INCLUDING AFFF) OR PROTEIN FOAMS MAY FUNCTION, BUT MUCH LESS EFFECTIVELY. DO NOT USE DIRECT WATER STREAM, WHICH WILL

SPREAD FIRE.

FLASH POINT......NONE. BOILED AT 95 (C).

SPECIAL FIRE FIGHTING PROCEDURES...... FIRE FIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING,

INCLUDING SELF-CONTAINED BREATHING EQUIPMENT.

UNUSUAL FIRE AND EXPLOSION HAZARDS....... ISOLATE AND RESTRICT AREA ACCESS. USE WATER SPRAY TO COOL

FIRE-EXPOSED CONTAINERS AND STRUCTURES. FIGHT FIRE FROM A SAFE DISTANCE AND FROM A PROTECTED LOCATION. CONSIDER USE OF UNMANNED HOSE HOLDER OR MONITOR NOZZLES.

WITHDRAW IMMEDIATELY IN CASE OF RISING SOUND FROM VENTING SAFETY DEVICES OR DISCOLOURATION OF TANK. BURNING LIQUIDS

MAY BE MOVED BY FLUSHING WITH WATER TO PROTECT

PERSONNEL AND MINIMIZE PROPERTY DAMAGE. MOVE CONTAINERS FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. CONTAINER MAY RUPTURE FROM GAS GENERATION IN A FIRE SITUATION. VIOLENT STEAM GENERATION OR ERUPTION MAY OCCUR UPON APPLICATION

OF DIRECT WATER STREAM TO HOT LIQUIDS.

ORGANIC ACIDS. SOME METALLIC OXIDES. PHOSPHORIC ACID.

PHOSPHORUS OXIDES.

SECTION 06: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES.....

WEAR APPROPRIATE PROTECTIVE EQUIPMENT. PREVENT ENTRY INTO SEWERS OR STREAMS, DIKE IF NEEDED. SMALL SPILLS: SOAK UP WITH ABSORBENT MATERIAL AND SCOOP INTO CONTAINERS. LARGE SPILLS: PREVENT CONTAMINATION OF WATERWAYS. DIKE AND PUMP INTO SUITABLE CONTAINERS. CLEAN UP RESIDUAL WITH ABSORBENT MATERIAL, PLACE IN APPROPRIATE CONTAINER AND FLUSH WITH WATER.

SECTION 07: HANDLING AND STORAGE

HANDLING PROCEDURES AND EQUIPMENT.....

FOR INDUSTRIAL USE ONLY. HANDLE AND OPEN CONTAINERS WITH CARE. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. DO NOT INGEST. AVOID INHALATION OF CHEMICAL. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS PRODUCT RESIDUES. KEEP THE CONTAINERS CLOSED WHEN NOT IN USE. PROTECT AGAINST PHYSICAL DAMAGE. USE APPROPRIATE PERSONNEL PROTECTIVE EQUIPMENT. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. SPILLS OF THESE ORGANIC LIQUIDS ON HOT FIBROUS INSULATIONS MAY LEAD TO LOWERING OF THE AUTOIGNITION TEMPERATURE POSSIBLY RESULTING IN SPONTANEOUS COMBUSTION. STORE IN A COOL, DRY, WELL-VENTILATED AREA, AWAY FROM HEAT

STORAGE REQUIREMENTS.....

AND IGNITION SOURCES. PLACE AWAY FROM INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH GOOD INDUSTRIAL

PRODUCT: PRISM Page 3

> PRACTICES. STORE IN THE FOLLOWING MATERIALS: CARBON STEEL. STAINLESS STEEL. PHENOLIC LINED STEEL DRUMS. DO NOT STORE IN ALUMINUM, COPPER, COPPER ALLOYS AND GALVANIZED CONTAINERS. AWAY FROM ACIDS. STORE AWAY FROM OXIDIZING AGENTS.

SECTION 08: EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROL..... PROVIDE GENERAL AND/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE LEVELS BELOW THE EXPOSURE GUIDELINES.

PERSONAL PROTECTIVE EQUIPMENT:

SKIN PROTECTION

ALL CLEANABLE IMPERVIOUS GLOVE TYPES ARE ACCEPTABLE. SKIN CONTACT SHOULD BE PREVENTED THROUGH THE USE OF SUITABLE PROTECTIVE CLOTHING, GLOVES AND FOOTWEAR, SELECTED FOR CONDITIONS OF USE AND EXPOSURE POTENTIAL. CONSIDERATION MUST BE GIVEN BOTH TO DURABILITY AS WELL AS PERMEATION

RESISTANCE.

SAFETY GLASSES WITH SIDE SHIELDS. AVOID CONTACT WITH EYES. EYE/FACE PROTECTION

WEAR CHEMICAL GOGGLES IF THERE IS THE POSSIBILITY OF

CONTACT OR SPLASHING IN THE EYE.

RESPIRATORY PROTECTION..... IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE AN APPROPRIATE NIOSH-APPROVED RESPIRATOR, NIOSH-APPROVED

ATMOSPHERE-SUPPLYING RESPIRATOR OR A NIOSH-APPROVED AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER IS RECOMMENDED. IN CASE OF SPILL OR LEAK RESULTING IN UNKNOWN CONCENTRATION, USE NIOSH

APPROVED SUPPLIED AIR RESPIRATOR.

ENSURE THAT EYEWASH STATIONS AND SAFETY SHOWERS ARE WORK/HYGIENE PRACTICES

PROXIMAL TO THE WORK-STATION LOCATION. USE GOOD PERSONAL HYGIENE PRACTICES. WASH HANDS BEFORE EATING, DRINKING,

SMOKING, OR USING TOILET FACILITIES.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... LIQUID APPEARANCE & ODOUR..... MILKY WHITE COLOUR - SLIGHT AMMONIA ODOUR ODOUR THRESHOLD..... N.AV.

SPECIFIC GRAVITY..... ~1.029 VAPOUR PRESSURE (MMHG)...... N.AV. EVAPORATION RATE......N.AV. BOILING POINT..... N.AV. FREEZING/MELTING POINT PH.....

SOLUBILITY IN WATER (% W/W)..... SOLUBLE. COEFFICIENT OF WATER/OIL DISTRIBUTION

SECTION 10: STABILITY AND REACTIVITY

STABLE UNDER NORMAL OPERATING CONDITIONS.

CONDITIONS TO AVOID..... DO NOT DISTILL TO DRYNESS. PRODUCT CAN OXIDIZE AT ELEVATED

TEMPERATURES. GENERATION OF GAS DURING DECOMPOSITION

CAN CAUSE PRESSURE IN CLOSED SYSTEMS.

STRONG ACIDS, STRONG BASES, STRONG OXIDIZERS, ALKALINES. INCOMPATIBILITY (MATERIALS TO AVOID)..... HAZARDOUS DECOMPOSITION PRODUCT..... CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES, KETONES.

ORGANIC ACIDS. SOME METALLIC OXIDES. PHOSPHORIC ACID.

PHOSPHORUS OXIDES.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMITS	SEE SECTION 3.
IRRITANCY OF MATERIAL	SEE SECTION 3.
LD50	SEE SECTION 3.
LC50	SEE SECTION 3

ECOLOGICAL INFORMATION N.AV.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL...... IN ACCORDANCE WITH MUNICIPAL, PROVINCIAL AND FEDERAL

REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

 TDG CLASSIFICATION
 N.AP.

 UN NUMBER
 N.AP.

 PACKGING GROUP
 N.AP.

SECTION 15: REGULATORY INFORMATION

WHMIS CLASSIFICATION D2B

CPR COMPLIANCE THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE

HAZARD CRITERIA OF THE CANADIAN CONTROLLED PRODUCTS

REGULATIONS (CPR) AND THE MSDS CONTAINS ALL THE

INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

PREPARATION DATE: JULY 1, 2016

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE